

Tabella ASTM dimensioni e spessori tubi

DN	Ø est.	Std	XS	XXS	sch.10	sch.20	sch.30	sch.40	sch.60	sch.80	sch.100	sch.120	sch.140	sch.160
1/8"	10.29	1.73	2.41	-	-	-	-	1.73	-	2.41	-	-	-	-
1/4"	13.72	2.23	3.02	-	-	-	-	2.23	-	3.02	-	-	-	-
3/8"	17.14	2.31	3.20	-	-	-	-	2.31	-	3.20	-	-	-	-
1/2"	21.34	2.77	3.73	7.47	-	-	-	2.77	-	3.73	-	-	-	4.75
3/4"	26.67	2.87	3.91	7.82	-	-	-	2.87	-	3.91	-	-	-	5.54
1"	33.40	3.38	4.55	9.09	-	-	-	3.38	-	4.55	-	-	-	6.35
1"1/4	42.16	3.56	4.85	9.70	-	-	-	3.56	-	4.85	-	-	-	6.35
1"1/2	48.26	3.68	5.08	10.16	-	-	-	3.68	-	5.08	-	-	-	7.14
2"	60.32	3.91	5.54	11.07	-	-	-	3.91	-	5.54	-	-	-	8.71
2"1/2	73.02	5.16	7.01	14.02	-	-	-	5.16	-	7.01	-	-	-	9.52
3"	88.90	5.49	7.62	15.24	-	-	-	5.49	-	7.62	-	-	-	11.12
3"1/2	101.60	5.74	8.08	-	-	-	-	5.74	-	8.07	-	-	-	-
4"	114.30	6.02	8.56	17.12	-	-	-	6.02	-	8.56	-	11.12	-	13.49
5"	141.30	6.55	9.52	19.05	-	-	-	6.55	-	9.52	-	12.70	-	15.87
6"	168.27	7.11	11.97	21.94	-	-	-	7.11	-	11.97	-	14.27	-	18.24
8"	219.07	8.18	12.70	22.22	-	6.35	7.04	8.18	10.31	12.70	15.06	18.24	20.62	23.01
10"	273.05	9.27	12.70	-	-	6.35	7.80	9.27	12.70	15.06	18.24	21.41	25.40	28.57
12"	323.85	9.52	12.70	-	-	6.35	8.38	10.31	14.27	17.45	21.41	25.40	28.57	33.32
14"	355.60	9.52	12.70	-	6.35	7.92	9.52	11.12	15.06	19.05	23.80	27.76	31.75	35.71
16"	406.40	9.52	12.70	-	6.35	7.92	9.52	12.70	16.66	21.41	26.19	30.94	36.52	40.46
18"	457.20	9.52	12.70	-	6.35	7.92	11.12	14.27	19.05	23.80	29.36	34.92	39.67	45.24
20"	508.00	9.52	12.70	-	6.35	9.52	12.70	15.06	20.62	26.19	32.54	38.10	44.45	49.99
24"	609.60	9.52	12.70	-	6.35	9.52	14.27	17.45	24.59	30.94	38.89	46.02	52.37	59.51
30"	762.00	-	-	-	7.92	12.70	15.87	-	-	-	-	-	-	-

Tutte le misure a parte il diametro nominale sono espresse in mm.